

## Conwed Fibers® Hydro Mulch® 1000 with TriFlo™ Wood Fiber

Now with  
**TriFlo™!**

Makes the best hydraulic  
mulch even better!

- Improves moisture retention
- Improves the suspension of mulch, seed and fertilizer within the slurry and prevents the dewatering of the fiber mulch
- Improves the application of hydraulic mulch in a more uniform layer for better coverage and enhanced product performance
- Improves application efficiency by increasing shooting distance and enhancing hose performance—greatly reducing downtime associated with clogging



Thermally Refined® manufacturing process provides a  
higher quality wood mulch and unsurpassed performance.

- Conwed Fibers® Hydro Mulch® 1000 with TriFlo™ provides maximum soil coverage due to its 100% Thermally Refined wood fiber
- Utilizes heat and pressure that breaks wood down into more fibrous material with greater surface area that results in better yield and coverage
- Delivers up to 50% more water-holding capacity than atmospherically refined wood mulches
- Creates an interlocking matrix for better erosion control protection and allows for improved oxygen transfer
- Creates a near perfect environment for faster germination



### Product Composition:

	<u>Slope Gradient/Condition</u>	<u>Rate</u>
Thermally Refined® Wood Fibers (minimum) – 87%± 3%	≤ 4H:1V	2000 lb/ac [2300 kg/ha]
Proprietary Emulsifying Agents (TriFlo) – 1% ± 0.5%	> 4H:1V and ≤ 3H:1V	2500 lb/ac [2800 kg/ha]
Moisture Content – 12% ± 3%	> 3H:1V and ≤ 2H:1V	3000 lb/ac [3400 kg/ha]
[40] 50-lb [23 kg] bales per pallet		



PROFILE Products LLC · 750 Lake Cook Road · Suite 440 · Buffalo Grove, IL 60089  
 Technical Assistance: 800-508-8681  
[www.conwedfibers.com](http://www.conwedfibers.com)